

Dx Series by Shermann

Bx215



Compact, highly portable LF cabinet with 2 powerful 15" bass drivers

Optional extras include pole mount adapter and rear mounted swivel castors c/w additional handles.

Use with SHERMANN Audio Dx cabinets to form a cost-effective, powerful, high quality PA or Disco rig.

Components

Wiring	2.5mm multi-strand copper
Castors (option)	4 x 100mm swivel type on back
LF drivers	Steel framed 15" / 3" voice coil

Connections

Speakon NL4	pin 1+ hot / pin 1- cold
Speakon NL8	pin 1+ hot / pin 1- cold

Crossover/filter frequencies

External:	High pass: -3dB @ 30Hz / 8th order
External:	Low pass: 110 Hz (within SHERMANN Audio systems)

Specifications

System

Format	Ported enclosure
Nom' impedance	4 ohm
Rec' amp' power @ 4ohm	450-800 watts rms
Programme power	1,200 watts

Performance

Sensitivity @ 1w/1m	100 dB
Maximum output	130dB @ 1m
Frequency response	40 Hz - 130Hz
Dispersion (>2.5khz)	N/a

Components

Drive unit (LF)	380 mm (15") x 2
-----------------	------------------

Dimensions

Height	883 mm
Depth	608 mm
Width	577 mm
Depth over castors (option)	736 mm
External volume	298 lts
Weight	62.8 Kgs

Mechanical

Connectors	"Speakon" NL4 x 2
(Option)	"Speakon" NL8 x 2
Castors (option) *	4 x 100mm swivel
Handles	Steel bar type
Stand mount (fitted)	35mm
Stand mount option*	32 or 38mm diameter
Finish	TRC or TPC
Foam Front / Welded	
Grille	Standard fitting

Please note

We would like to draw your attention to the likelihood of hearing damage from prolonged exposure to high sound pressure levels.

Care should be taken when using cabinets in close proximity to the audience, musicians or artists.

For further information on the safe operation of any Syrious or SHERMANN Audio product please fax, call or email us - contact details are shown below.

* Options must be requested at time of ordering.



Shermann

Unit 35, Vastre Enterprise Park
Newtown, Powys,
SY16 1DZ

Tel: +44 (0)8456 44 22 09
Fax: +44 (0)1686 623 233
Email: sales@shermann.com
Web: www.shermann-audio.com