

# D-Series by SHERMANN Audio

## D450

(discontinued model - replacement parts normally in stock except 15"; recone only)

**Shermann's D-450** is a two way, multi-role compact system supplied in passive drive format.

This model is fitted with a GSA1/35 stand mount adaptors and a GS-TA3 flying track/safety set for use with **Shermann** GS-F3 flying brackets or **Shermann** GS-W3 wall brackets.

**D-450's** offer the end user the widest possible range of uses and benefits - it's an entirely cost-effective, high quality product.



**D-450** (left) in wedge format with LF drivers placed together for increased coupling and (below) in FOH format on LS-22 speaker stands.

As a FOH pa unit the D-450 may be used for a wide variety of applications including theatres, conferences venues, churches, band PA system (with **Shermann** bass units if required) and AV in schools & colleges.

As a stage wedge the D-450 is designed for use in applications where a powerful, full range foldback speaker or side-fill is required.



**The D-450 is equipped with a powerful 15" bass/mid driver which incorporates a substantial magnet assembly and 3" voice coil.**

**Upper midrange & HF response is handled by **Shermann's** GS25F1 / GHF-2 driver & horn assembly.**

**An advanced ferro-fluid installed within the magnetic gap of all **Shermann** compression drivers improves long-term reliability by reducing heat build-up within the voice coil assembly.**

All **Shermann** products are built to the highest standards and the D-450 is no exception.

Constructed externally from 18mm birch plywood the loudspeaker baffle thickness is 25mm for ultimate rigidity and performance.

**Connections**  
**Speakon NL4** pin 1+ **hot** / pin 1- **cold** (2+ 2- to order)

**Crossover frequencies**  
**Internal:** not applicable; passive drive  
**External:** 4th order 100 - 125Hz (with **Shermann** bass systems)

### Technical Specifications

#### System

Format	2 way Passive
Network	PCN-3
Nom' impedance	8 ohm
Hi-pass filter (-3dB point)	35Hz / 4th order
Rec' amp' power @ 8ohm	250 - 450 watts rms
Maximum peak power	500 watts

#### Performance

Sensitivity @ 1w/1m	100 dB
Maximum output	126 dB @ 1m
Frequency response	50 Hz - 18.5 KHz
Dispersion (2khz up)	70° x 40°

#### Components

Drive unit (LF/MF)	380 mm (15")
Drive unit (HF)	25mm comp' driver
Horn unit	<b>Shermann</b> GHF-2

#### Dimensions

Height	647 mm (25-50")
Depth	378 mm (14-88")
Width	445 mm (17-50")
Apex height (as wedge)	465 mm (18-30")
External volume	107 lts ( 3-8 ft <sup>3</sup> )
Weight	30-5 Kgs ( 67 lbs)

#### Mechanical

Connectors	"Speakon" NL4 x 2
Flying points (fitted)	GS-TA3
Stand mount (fitted)	GSA1/35
Handle	Flip type
Finish	Black carpet

#### Please note

We would like to draw your attention to the likelihood of hearing damage from prolonged exposure to high sound pressure levels.

Care should be taken when using cabinets in close proximity to the audience, musicians or artists. For further information on the safe operation of any **Shermann** product please fax, call or email us - contact details are shown below.

\* Options must be requested at time of ordering.



### Shermann Audio

Unit 35, Vastre Enterprise Park,  
Newtown, Powys.  
SY16 1DZ

Tel: +44 (0)8456 44 22 09 (01686 622 997)

Fax: +44 (0)1686 623 233

Email: sales@shermann.com

Web: [www.shermann-audio.com](http://www.shermann-audio.com)