

# LM-Series by SHERMANN Audio

## LM301

*(discontinued model - replacement parts normally in stock except 12"; recone only)*

**Shermann's LM301** is a powerful, low profile dedicated stage wedge supplied in three-way passive drive format and a non-reflective black finish.

It features an efficient 12" bass driver plus a co-axially mounted 1" HF compression driver and a 6.5" midrange unit.

With superior vocal projection qualities and advantageous high gain before feedback the LM-301 represents excellent value in a truly compact package.



The LM-Series has been designed for use in the widest possible range of applications offering very high performance in a rugged but unobtrusive package.

**Shermann's LM-301** combines a low apex height with high sonic quality making it ideal for vocal and music foldback for use in Theatres, TV Studios, Concert stages and Places of Worship.

The **LM-301** is equipped with a powerful 12" bass/mid driver which incorporates a substantial magnet assembly and 2.5" voice coil.

Midrange response is handled by **Shermann's** GM17/50 cone mid unit whilst a GS25BC1 co-axially mounted compression driver handles the high frequencies.

An advanced ferro-fluid installed within the magnetic gap of all **Shermann** compression drivers improves long-term reliability by reducing heat build-up within the voice coil assembly.

**Shermann's** LM-301 is built to the highest standards and incorporates sustainable or recyclable materials wherever possible.

High grade 15mm baltic birch plywood is utilised for the outer shell whilst the loudspeaker baffle thickness is 25mm for ultimate rigidity.

### Connections

**Speakon NL4** pin 1+ **hot** / pin 1- **cold** (2+ 2- to order)

### Crossover frequencies

**Internal:** not applicable; passive drive

**External:** 4th order 110Hz (with **Shermann** bass systems)

### Technical Specifications

#### System

Format	3 way Passive
Network	PCN-4
Nom' impedance	8 ohm
Hi-pass filter (-3dB point)	40Hz / 4th order
Rec' amp' power @ 8ohm	175 - 300 watts rms
Maximum input power	350 watts

#### Performance

Sensitivity @ 1w/1m	100 dB
Maximum output	125 dB @ 1m
Frequency response	65 Hz - 18.5 KHz
Dispersion (>2.5kHz)	70° x 70°

#### Components

Drive unit (LF/MF)	305 mm (12")
Drive unit (HF)	6.5" cone mid
Horn unit	25 mm / Co-ax

#### Dimensions

Height	362 mm (14.25")
Depth	318 mm (12.50")
Width	575 mm (22.63")
Apex height	344 mm (13.56")
External volume	58.2 lts (2.10ft <sup>3</sup> )

#### Mechanical

Connectors *	"Speakon" NL4 x
Flying points (option) *	2GS-TA3
Stand mount (option) *	GSA1/35
Handle	2 x large flip
Finish*	Black carpet

#### Please note

We would like to draw your attention to the likelihood of hearing damage from prolonged exposure to high sound pressure levels.

Care should be taken when using cabinets in close proximity to the audience, musicians or artists.

For further information on the safe operation of any **Shermann** product please fax, call or email us - contact details are shown below.

\* Options must be requested at time of ordering.



### Shermann Audio

Unit 35, Vastre Enterprise Park,  
Newtown, Powys.  
SY16 1DZ

Tel: +44 (0)8456 44 22 09 (01686 622 997)

Fax: +44 (0)1686 623 233

Email: sales@shermann.com

Web: [www.shermann-audio.com](http://www.shermann-audio.com)